

Preferred Industrial Supply

MATERIAL SAFETY DATA SHEET

EMERGENCY #: CANUTEC (613) 996-6666

PRODUCT IDENTIFICATION AND PREPARATION INFORMATION

PRODUCT NAME: Orange Grease Blaster

EFFECTIVE DATE: March 11, 2010

WHMIS CLASS: Class A; Class B – Div 5; Class D – Div 2B

T.D.G. CLASSIFICATION: Consumer Commodity ORM-D

MATERIAL USE: Degreaser

HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS #	%WT	TWA/TLV	LD 50	LC 50
Citrus Terpene	5989-27-5	20-30	400ppm	4400 mg/kg Oral/Rat	N/D
Diethylene Glycol Monoethyl Ether	111-90-0	01-10	25 ppm	N/D	N/D
Diethanolamine	111-42-2	01-10	.46 ppm	N/D	N/D
Liquified Petroleum Gas	68476-85-7	10-30	1000 ppm	N/D	N/D

PHYSICAL DATA

DATA BELOW BASED ON AEROSOL CONCENTRATE ONLY:

BOILING POINT: ~ 100° C

pH: 10.2

VAPOR DENSITY(AIR=1): >1

SOLUBILITY IN WATER: Complete

SPECIFIC GRAVITY (H₂O=1)@23° C: 0.98

APPEARANCE/ODOR: White Foam, Citrus Fragrance

DATA BELOW BASED ON TOTAL CONTENTS:

VAPOR PRESSURE OF CAN (psig @20° C): 60

TOTAL VOC %: ~40.2%

FIRE AND EXPLOSION DATA

FLASH POINT (of Concentrate Only): 52° C (T.O.C)

FLAMMABILITY (as per Flame Projection Test): Flammable Spray

EXTINGUISHING MEDIA: Foam, CO₂, Dry Media

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Exposure to temperature above 50° C may cause bursting.

REACTIVITY DATA

STABILITY: Material Stable.

HAZARDOUS POLYMERIZATION: Will not Occur.

INCOMPATIBILITY: Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide

FIRST AID

EYES: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN: Wash with soap and water. If irritation persists seek medical attention.

INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY: Eyes contact (), Skin contact (), Skin absorption (), Inhalation (), Ingestion ()

EFFECTS OF ACUTE EXPOSURE:

EYES: May cause slight irritation but does not injure eye tissue.

SKIN: Frequent or prolonged contact may cause irritation.

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.

EFFECTS OF CHRONIC EXPOSURE:

SKIN:

IRRITANCY:

SENSITIZATION:

CARCINOGENICITY: Non Hazardous by WHMIS Criteria

REPRODUCTIVE TOXIN: N/D

TERATOGENICITY: N/D

MUTAGENICITY: N/D

SYNERGISTIC MATERIALS: N/D

EXPOSURE LIMITS: N/D

PREVENTATIVE MEASURES

RESPIRATORY PROTECTION: None needed for proper use in accordance with label directions.

VENTILATION: Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.

PROTECTIVE GLOVES: None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.

EYE PROTECTION: None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.

ENGINEERING CONTROLS:

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, Provincial and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, Provincial and local authorities for approved procedures.

STORAGE REQUIREMENTS: KEEP OUT OF REACH OF CHILDREN. For Industrial and Institutional use only. Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 49° C.

N/AP= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · N/AV=NOT AVAILABLE
<=LESS THAN - >=MORE THAN

HMIS HAZARD RATING INFORMATION

FIRE	REACTIVITY	HEALTH	PERSONAL PROTECTION
2	0	1	B

0 – Minimal, 1- Slight, 2 – Moderate, 3 – Serious, 4 – Extreme.

DISCLAIMER: Information for this material safety data sheet was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases, data is not available and is so stated. Since conditions of actual product use are beyond the control of the supplier, it is assumed that the user of this material has been fully trained according to the mandatory requirements of WHIMIS. No warranty, expressed or implied is made, and supplier will not be liable for any losses, injuries, or consequential damage that may result from the use or reliance on any information contained in this form.

PREFERRED INDUSTRIAL

#3160-21331 GORDON WAY
RICHMOND, BC V6W 1J9
1-604-231-6030