



SUPERMETALIUM SOS (SUPER OIL SUPPLEMENT) EXTREME PRESSURE OIL CONCENTRATE

SPECIFICATIONS

Specific Gravity @ 60°F	1.06	ASTM	D-1298
Flash Point (C.O.C.) °C.....	138	ASTM	D-1310
Pour Point °C.....	-40	ASTM	D-97-66
Viscosity @ 40°C.....	29.95	ASTM	D-445
Viscosity @ 100°C.....	4.464	ASTM	D-445
Viscosity Index	177	ASTM	D-2270-79
Water % v/v.....	0	ASTM	D-4007
Solids % v/v.....	0	ASTM	D-4007
Copper Strip Corrosion.....	1a	ASTM	D-130-80
T.B.N.	1.57	ASTM	D-664-81
Appearance.....	Dark Amber		
Odour	Oil		

FEATURES

1. Versatile and fully compatible with all API approved oils
2. Blends readily in Synthetic and Mineral base lubricants
3. Stable formulation fortifies these characteristics to the host lubricant:
 - Extreme Pressure load Carrying ability
 - Enhanced Detergency
 - Superior Corrosion Resistance
4. Non-solid compound does not build up beyond a single, monomolecular layer
5. Highly effective at low treatment ratio
6. Provides unsurpassed friction/wear reduction
7. Lowers operating temperatures and extends equipment life
8. Provides optimum lubricity to a wide variety of severe duty automotive, trucking, industrial, agricultural, mining and construction equipment.